


# CVS1K Series

Non-lube Type:  
 ø40, ø50, ø63

## Construction



\* The numbers correspond with those in the "Construction" of the CVS1K series in the Best Pneumatics catalog.

### Seal Kit List

No.	Description	Material	Note
27	Piston seal	NBR	<b>29, 32, 34 and 35 are non-replaceable parts, so they are not included in the seal kit.</b>
28	Rod seal		
29	Cushion seal		
30	Cylinder tube gasket		
31	Cushion valve seal		
32	Piston gasket		
33	Pipe gasket		
34	Speed adjustment valve seal		
35	Gasket		
36	Valve port gasket		

### Replacement Parts: Seal Kit

Bore size (mm)	Part no.	Contents
40	CVS1K40-PS	Set of nos. 27, 28, 30, 31, 33, 36
50	CVS1K50-PS	
63	CVS1K63-PS	

- \* The seal kit includes 27, 28, 30, 31, 33, 36. Order the seal kit based on each bore size.
- \* The seal kit includes a grease pack (ø40, ø50: 10 g, ø63 or more: 20 g). Order with one of the following part numbers when only the grease pack is required.  
**Grease pack part no.: GR-S-010 (10 g), GR-S-020 (20 g)**

### Disassembly/Replacement

#### 1. Please consult with SMC when the rod seal is to be replaced.

When the rod seal is to be replaced, make sure that the seal's width across flats matches that of the non-rotating guide. A rod seal may allow air leakage depending on the position where it is installed. Therefore, please consult with SMC when a rod seal is to be replaced.

#### 2. Do not replace the non-rotating guide.

Since the non-rotating guide is press fitted, the entire cover assembly needs to be replaced instead of a single part.

Actuators

Modular F.R.L.  
Pressure Control Equipment

Air Preparation  
Equipment

Industrial Filters

Replacement  
Procedure

Actuators

Modular F.R.L.  
Pressure Control Equipment

Industrial Filters